



BSS tractor trailers

## BSS tractor trailers

BSS tractor trailers represent an old proven concept in a modern design. BSS trailers are characterized especially by their robust structure, perfect manufacturing and amply dimensioned high-quality components.

The trailers are prepared in every respect for the long-term load in agricultural or municipal operations.

BSS trailers always have a three-side tipping body, Fuhrmann pressed sideboards, a variable sideboard opening and closing system, a chassis frame made of closed sections, automatic parking brake, automatic brake pressure control device, a discharge hopper in the rear panel, and a sufficiently dimensioned turntable and are, due to their suspended axles, approved for a speed limit of 40 km/hour.

For increased capacity, both BSS trailer designs can be equipped with a second sideboard row (600 mm high for trailer BSS 14.10; 600 mm high or alternatively 800 mm high for trailer BSS 18.14). Other "optional equipment" items are, for example, service footbridge or spare wheel holder elements, rolling tarpaulins (including the tarpaulin structure) or colours on request.

Technical parameters	BSS 14.10	BSS 18.14
Number of axles (pcs)	2	2
Maximum total allowable weight (kg)	14 000	18 000
Maximum body volume (m <sup>3</sup> )	13	20
Loading area length (mm)	4 610	5 200
Loading area width (mm)	2 340	2 400
Total length (mm)	6 830	7 470
Total width (mm)	2 550	2 550
Speed limit (km/hour)	40	40

